

102011

MATERIAL SAFETY DATA SHEET

IDENTITY (As used on label and list): TRAVELLERS PREMIUM UNIVERSAL TRACTOR TRANS-HYDRAULIC FLUID, ska (TRAVELLERS PREMIUM UNIVERSAL TRACTOR HYDRAULIC FLUID)

PRODUCT CODE: TS44HT2G, TS44HT5P, TS44HT6P, TSG4HT5P

NFPA Hezard Identification

0 - Least

1 - Slight

2- Moderate 3 - High

Health: 0

Fire: 1

Reactivity: 0

Section I - General Information

Warren Distribution, Inc. 2849 River Road Council Bluffs, IA 51501 Information (402) 341-9397

Emergency

(402) 677-1331

Chemtree

(800) 424-9388

Reviewed: 05/13/04

4 - Extreme

on judgedients			
NATE:	9%	C*#	ACT A DET

COMPONENT NAME
Lubricating Oil Base Stock

% >94

<6

64742-54-7 or 64742-65-0

5mg/m3*

ACGIH TLV 5mg/m3*

Proprietary additives
* Numbers are for oil mist.

mixture

none est.

none est.

NON-HAZARDOUS INGREDIENTS

No IARC, NIP, OSHA and ACGIH listed carcinogens.

Section III - Hazards Identification

EYE CONTACT: Contact with eyes may cause eye initation.

SKIN CONTACT: Prolonged or repeated contact may result in skin irritation or demnatitis.

INHALATION: Breathing oil mist in concentrations that exceed the TLV and PEL may result in respiratory discomfort and traitation.

INGESTION: Although this product has a low order of acute oral toxicity, aspiration of minute amounts into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.

CARCINOGENICITY: This product has not been classified as a carcinogen or probable carcinogen by OSHA, NTP, or lARC.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: May cause skin, eye, or respiratory irribation

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None recognized

Page 1 of 4

Printed in the U.S.A.

£594-63

OTHER HEALTH INFORMATION: None

Section IV - First Aid Procedures

EYE CONTACT: If splashed into eyes, flush with water for 15 minutes or until infrastion subsides. Get medical attention if irritation possists.

SKIN CONTACT: Remove contaminated clothing. Wash skin thoroughly With soap and water. Get medical attention if irritation persists.

INHALATION: If overcome by vapor from hot product, immediately remove victim to fresh air. If breathing has stopped, administer artificial respiration. Call for medical attention. If overexposed to oil mist, remove from further exposure.

INGESTION: DO NOT inchoos vomiting, call medical attention immediately.

Section V - Fire and Explosion Hazard Luta

Flash Point (deg F): 420 Method Used: COC Flammable or Explosive Limits (approximate % by volume in 2ir) LEL: 0.9 UEL: 7.0

EXTINGUISHING MEDIA: Use water spray, dry chemical, form, or carbon dioxide. Use water to keep fireexposed containers cool. Water spray may be used to flush spills away from exposures and to disperse vapors from spills or leaks.

SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus may be required.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known

Section VI - Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Add sand, earth, or other suitable absorbent to spill area. Keep product out of sewers and waterways by damming or impounding.

Section VII - Handling and Storage

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place with adequate ventilation. Do not expose to extreme temperatures or flarmes.

OTHER PRECAUTIONS: None

Section VIII Expense Controls/Personal Protection

RESPIRATORY PROTECTION: Use supplied-zir respiratory protection in confined or enclosed space, if

VENTILATION: Use local exhaust to capture vapor, mists or fumes, if necessary. Provide ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. Use explosion-proof equipment.

PROTECTIVE GLOVES: Use neoptone gloves, if needed, to avoid prolonged or repeated skin contect.

EYE PROTECTION: Wear goggles if there is likelihood of contact with eye(s).

OTHER PROTECTIVE EQUIPMENT: Use neoprene aprox or other clothing, if needed, to avoid prolonged or repeated skin contact.

WORK PRACTICES/ENGINEERING CONTROLS: Keep containers closed when not in use.

Castelle ?->

PERSONAL HYGIENE: Wash skin thoroughly after contact, before breaks and meals, and at the end of the work period. Thoroughly clean contaminated clothing, including shoes, before reuse.

Section IX- Physical/Chemical Characteristics Vapor Pressure (mm Hg): < 01 Specific Chavity (H2O=1): .887 Boiling Point (deg F): ND Solubility in Water: Insoluble Vapor Density (Air=1): 11/2 Melting Point (deg F): <-35 Evaporation Rate (n-butyl Acetate=1): <01 APPEARANCE AND ODOR: Light unber liquid, mild petroleum odor. Section X - Reactivity Data STABILITY: Stable CONDITIONS TO AVOID: None INCOMPATIBILITY (MATERIALS TO AVOID): strong oxidants such as liquid chlorine, concentrated oxygen, sedium hypochlerite er calcium hypochlerite HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Furnes, smoke, carbon dioxide, aldehydes and other decomposition products, in the case of incomplete combustion. HAZARDOUS POLYMERIZATION: Will not occur Section XI - Toxicological Information See Section IV Section XII - Ecological Information

WASTE DISPOSAL METHOD: Place in an appropriate disposal facility in compliance with local regulations.

Section XIV - Transport Information

Section XIII - Disposal Considerations

NOT A REGULATED ITEM ACCORDING TO DOT.

Section XV-Regulatory Information

SARA SECTION 313: This product contains from 1.0 to 1.5 % zine compounds WHMIS classification for product: This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

This material safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we received from sources outside our company and we believe that information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safety and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.