Printing date 11/12/2014 Revised On 11/12/2014

1 Identification of the substance and manufacturer

Trade name: SCHOOL BUS YELLOW

80944 **Product code:**

PC9a Paints and coatings. **Product category**

Kimball Midwest Manufacturer/Supplier:

4800 Roberts Road Columbus, OH 43228 800-233-1294 www.kimballmidwest.com

Emergency telephone number: ChemTrec: 800-424-9300



2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated. Press. Gas

Carc. 2 H351 Suspected of causing cancer. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness

GHS Hazard pictograms

GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness.

Obtain special instructions before use. **Precautionary statements**

Obtain special instructions before use.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

	Dangerous components:						
	Acetone	19.53%					
	propane	15.8%					
	barium sulphate, natural	9.33%					
	n-butane	9.28%					
	methyl isobutyl ketone	5.48%					
	Glycol Ether EP	5.27%					
	PM acetate	3.26%					
	Methyl Propyl Ketone	2.82%					
	xylene (mix)	2.46%					
	isobutyl acetate	1.93%					
13463-67-7	titanium dioxide	1.17%					

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. If symptoms persist, consult a After eye contact:

doctor.

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

Indication of any immediate medical

No further relevant information available. attention needed:

Printing date 11/12/2014 Revised On 11/12/2014

Trade name: SCHOOL BUS YELLOW

(Contd. of page 1)

5 Fire-fighting measures

Extinguishing agents: Special hazards:

CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.

Protective equipment for firefighters:

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures: Methods and material for containment and cleaning up: Use respiratory protective device against the effects of fumes/dust/aerosol.

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

•	ontrols/personal protection			
<u> </u>	with limit values that require monitoring at the workplace:			
67-64-1 Acet				
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm			
REL (USA)	Long-term value: 590 mg/m³, 250 ppm			
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm BEI			
74-98-6 prop				
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm			
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm			
TLV (USA)	refer to Appendix F			
	rium sulphate, natural			
PEL (USA)	Long-term value: 15* 5** mg/m³			
1 LL (00/1)	*total dust **respirable fraction			
REL (USA)	Long-term value: 10* 5** mg/m ³			
(/	*totăl dust **respirable fraction			
TLV (USA)	Long-term value: 5* mg/m³ *inhalable fraction; E			
106-97-8 n-b				
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm			
TLV (USA)	Short-term value: 2370 mg/m³, 1000 ppm			
	hyl isobutyl ketone			
PEL (USA)	Long-term value: 410 mg/m³, 100 ppm			
REL (USA)	Short-term value: 300 mg/m³, 75 ppm			
(30/1)	Long-term value: 205 mg/m³, 50 ppm			
TLV (USA)	Short-term value: 307 mg/m³, 75 ppm			
	Long-term value: 82 mg/m³, 20 ppm BEI			
108-65-6 PM				
	Long-term value: 50 ppm			
	hyl Propyl Ketone			
PEL (USA)	Long-term value: 700 mg/m³, 200 ppm			
REL (USA)	Long-term value: 530 mg/m³, 150 ppm			
TLV (USA)	Short-term value: 529 mg/m³, 150 ppm			
1330-20-7 xy				
PEL (USA)	Long-term value: 435 mg/m³, 100 ppm			
REL (USA)	Short-term value: 655 mg/m³, 150 ppm			
1122 (00/1)	Long-term value: 435 mg/m³, 100 ppm			
TLV (USA)	Short-term value: 651 mg/m³, 150 ppm			
, ,	Long-term value: 434 mg/m³, 100 ppm BEI			
110-19-0 isok	outyl acetate			
PEL (USA)	Long-term value: 700 mg/m³, 150 ppm			
REL (USA)	Long-term value: 700 mg/m³, 150 ppm			
TLV (USA) Long-term value: 713 mg/m³, 150 ppm				
Ingredients v	vith biological limit values:			
67-64-1 Acet	<u> </u>			

BEI (USA) 50 mg/L

Medium: urine

Time: end of shift Parameter: Acetone (nonspecific)

(Contd. on page 3)

(Contd. of page 2)

Printing date 11/12/2014 Revised On 11/12/2014

Trade name: SCHOOL BUS YELLOW

108-10-1 methyl isobutyl ketone

BEI (USA) 1 mg/L

Medium: urine Time: end of shift Parameter: MIBK

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas.

In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

Hand protection: Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance:
Odor:
Odor threshold:

PH-value:
Melting point/Melting range
Boiling point:

Flash point:

Aerosol.

Aromatic

Not determined.

Undetermined.

-44 °C (-47 °F)

-19 °C (-2 °F)

Flammability (solid gas):

Extremely flammability

Flammability (solid, gas): Extremely flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit:1.7 Vol %Upper Explosion Limit:10.9 Vol %Vapor pressure:Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapour density
Evaporation rate
Partition coefficient: n-octonal/water: Not determined.
Solubility:
Viscosity:
Not determined.
Not determined.
VoC content:
498.2 g/l / 4.16 lb/gl

VOC content (less exempt solvents): 47.4 % MIR Value: 1.10
Solids content: 32.7 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

2000 mg/kg (rbt)

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials:
Hazardous decomposition:

No further relevant information available.
No dangerous decomposition products known.

11 Toxicological information

LD50

Dermal

	9						
LD/LC50 values that are relevant for classification:							
106-97-8 r	106-97-8 n-butane						
	Inhalative LC50/4 h 658 mg/l (rat)						
108-10-1 r	108-10-1 methyl isobutyl ketone						
Oral		2100 mg/kg (rat)					
Dermal	LD50	16000 mg/kg (rab)					
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)					
108-65-6 F	108-65-6 PM acetate						
		8500 mg/kg (rat)					
Inhalative	LC50/4 h	35.7 mg/l (rat)					
1330-20-7	1330-20-7 xylene (mix)						
Oral	LD50	8700 mg/kg (rat)					

(Contd. on page 4)

Printing date 11/12/2014 Revised On 11/12/2014

Trade name: SCHOOL BUS YELLOW

(Contd. of page 3) Inhalative LC50/4 h 6350 mg/l (rat) 110-19-0 isobutyl acetate LD50 Oral 4763 mg/kg (rbt)

13463-67-7 titanium dioxide

Oral LD50 >20000 mg/kg (rat) >10000 mg/kg (rbt) Dermal LD50 Inhalative LC50/4 h >6.82 mg/l (rat)

Information on toxicological effects: No data available.

Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

IAINO (IIILEII	national Agency for Research on Cancery	
108-10-1	methyl isobutyl ketone	2B
1330-20-7	xylene (mix)	3
13463-67-7	titanium dioxide	2B

Hazardous for water, do not empty into drains.

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes. Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950

DOT Aerosols, flammable ADR 1950 Aerosols

Transport hazard class(es):

2.1 Class Marine pollutant: No

Special precautions for user: Warning: Gases

F-D,S-Ŭ **EMS Number:**

Packaging Group:

UN1950, Aerosols, 2.1 **UN "Model Regulation":**

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulphate, natural 108-10-1 methyl isobutyl ketone

1330-20-7 xylene (mix)

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

108-10-1 methyl isobutyl ketone

13463-67-7 titanium dioxide 100-41-4 ethyl benzene

CANADIAN ENVIRONMENTAL PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

•	• •	_	•	_,	•	 •	•	•	•	
F	P	Δ								

EPA:		
67-64-1	Acetone	
7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
108-10-1	methyl isobutyl ketone	I
	xylene (mix)	I
110-19-0	isobutyl acetate	D

16 Other information

Contact: Regulatory Affairs 11/12/2014 / -Date of preparation / last revision