Permatex

SAFETY DATA SHEET

Revision Date 11-Jun-2015 Version 3

1. IDENTIFICATION

Product identifier

Product Name HIGH TACK SPRAY-A-GASKET SEALANT 9 OZ.

Other means of identification

Product Code 80065 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Aerosol Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

<u>Manufacturer Address</u> <u>Distributor</u>

ITW Permatex Canada
10 Columbus Blvd. 35 Brownridge Road, Unit 1
Hartford, CT 06106 USA Halton Hills, ON Canada L7G 0C6

Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex

(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1

Label elements

Emergency Overview			
Danger			

Revision Date 11-Jun-2015

Causes skin irritation

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Extremely flammable aerosol



Appearance Red Physical state Liquid Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7).

The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0.1 % w/w 1,3-butadiene (EINECS No. 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the S-phrases (2-)9-16 (Table 3.2) should apply. This note applies only to certain complex oil-derived substances in Part 3

OZ.

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
PETROLEUM GASES, LIQUEFIED, SWEETENED	68476-86-8	30 - 60	*
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH.	64742-89-8	10 - 30	*
N-HEXANE	110-54-3	10 - 30	*
ETHYL ACETATE	141-78-6	1 - 5	*
ACETONE	67-64-1	1 - 5	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. If skin irritation persists, call a physician. Wash contaminated clothing

before reuse.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a physician.

Ingestion IF SWALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician.

Self-protection of the first aiderUse personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Extremely flammable. Heating causes rise in pressure with risk of bursting.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Revision Date 11-Jun-2015

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Ensure adequate ventilation, especially in confined areas.

Avoid contact with eyes and skin. Use personal protective equipment as required.

Environmental precautions

Environmental precautionsDo not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with

inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Take precautionary

measures against static discharges. Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wash

contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Incompatible materials Strong oxidizing agents, Alkalis

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-HEXANE	TWA: 50 ppm	TWA: 500 ppm	IDLH: 1100 ppm
110-54-3	S*	TWA: 1800 mg/m ³	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 180 mg/m ³
		(vacated) TWA: 180 mg/m ³	
ETHYL ACETATE	TWA: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
141-78-6		TWA: 1400 mg/m ³	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 1400 mg/m ³
		(vacated) TWA: 1400 mg/m ³	_

ACETONE	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	_
		(vacated) STEL: 2400 mg/m ³ The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors	
		(vacated) STEL: 1000 ppm	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Wear protective gloves and protective clothing. Skin and body protection

Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid **Appearance** Red Odor Solvent

Odor threshold No information available

Property Values Remarks • Method

Does not apply Hq

No information available Melting point / freezing point Boiling point / boiling range > 38 °C / 100 °F

Flash point < -18 °C / < 0 °FGives a flame projection at full valve opening or

flashback at any degree of valve opening

Air = 1

Evaporation rate Ether = 1

Flammability (solid, gas) No information available Flammability Limit in Air

Upper flammability limit: No information available Lower flammability limit: No information available

Not determined

Vapor pressure Vapor density >1

Relative density 0.755-0.765

Water solubility Negligible

Solubility in other solvents No information available **Partition coefficient** No information available **Autoignition temperature** No information available

No information available **Decomposition temperature** No information available Kinematic viscosity No information available Dynamic viscosity

Explosive propertiesOxidizing properties
No information available
No information available

Other Information

Softening pointNo information availableMolecular weightNo information available

VOC Content (%) 64.7%

Density
No information available
Bulk density
No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Alkalis

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May be harmful by inhalation.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis.

Ingestion Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary

edema and pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. 64742-89-8	-	= 3000 mg/kg (Rabbit)	-
N-HEXANE 110-54-3	= 25 g/kg(Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
ETHYL ACETATE 141-78-6	= 5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit)> 20 mL/kg (Rabbit)	-
ACETONE 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicityNo information available.
No information available.

Reproductive toxicity Product is or contains a chemical which is a known or suspected reproductive hazard. **Target Organ Effects** Product is or contains a chemical which is a known or suspected reproductive hazard.

Central nervous system, Eyes, Peripheral Nervous System (PNS), Respiratory system,

Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 53308 mg/kg
ATEmix (dermal) 5950 mg/kg
ATEmix (inhalation-dust/mist) 4008 mg/l
ATEmix (inhalation-vapor) 192000 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

45 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. 64742-89-8	4700: 72 h Pseudokirchneriella subcapitata mg/L EC50	-	-
N-HEXANE 110-54-3	-	2.1 - 2.98: 96 h Pimephales promelas mg/L LC50 flow-through	1000: 24 h Daphnia magna mg/L EC50
ETHYL ACETATE 141-78-6	3300: 48 h Desmodesmus subspicatus mg/L EC50	352 - 500: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 220 - 250: 96 h Pimephales promelas mg/L LC50 flow-through 484: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	560: 48 h Daphnia magna mg/L EC50 Static
ACETONE 67-64-1	-	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
PETROLEUM GASES, LIQUEFIED, SWEETENED	<=2.8
68476-86-8	
ETHYL ACETATE	0.6
141-78-6	
ACETONE	-0.24
67-64-1	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesThis material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging Do not reuse container.

Contaminated packaging Do not reduce container.

US EPA Waste Number D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
ETHYL ACETATE 141-78-6	-	Included in waste stream: F039	-	U112
ACETONE 67-64-1	-	Included in waste stream: F039	-	U002

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
N-HEXANE	Toxic
110-54-3	Ignitable
ETHYL ACETATE	Toxic
141-78-6	Ignitable
ACETONE	Ignitable
67-64-1	

14. TRANSPORT INFORMATION

DOT

UN/ID no UN 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.1

IATA

UN/ID no ID 8000

Proper shipping name: Consumer commodity

Hazard Class 9

IMDG

UN/ID no UN 1950

Proper shipping name: Aerosols, Limited Quantity (LQ)

Hazard Class 2.1

15. REGULATORY INFORMATION

International Inventories

TSCA Complies **DSL/NDSL** Complies **EINECS/ELINCS** Complies Not Listed. **ENCS** Complies **IECSC** Complies **KECL PICCS** Complies **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
N-HEXANE - 110-54-3	1.0
CADA 244/242 Heneral Catagorica	

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
N-HEXANE	5000 lb	-	RQ 5000 lb final RQ
110-54-3			RQ 2270 kg final RQ
ETHYL ACETATE	5000 lb	-	RQ 5000 lb final RQ
141-78-6			RQ 2270 kg final RQ
ACETONE	5000 lb	=	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
N-HEXANE 110-54-3	Х	X	X
ACETONE 67-64-1	Х	Х	X
ETHYL ACETATE 141-78-6	Х	X	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

NFPA Health hazards 2 Flammability 4 Instability 0 -

HMIS Health hazards 2 Flammability 4 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 11-Jun-2015

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet
