

Issuing date 25-Nov-2014

Revision Date 25-Nov-2014

Version 1.01

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING****Product identifier****Product name** 80-727 ELECTRO GUARD MOISTURE AND CORROSION BARRIER**Recommended use of the chemical  
and restrictions on use****Product code** F00491**Product Type** Extremely flammable aerosol  
**Synonyms** None**Supplier's details****Recommended Use** Moisture and Corrosion Barrier.  
**Uses advised against** No information available**Manufactured For:**  
Kimball Midwest  
4800 Roberts Rd.  
Columbus, OH 43228**Emergency telephone number**  
**Chemical Emergency Phone** Chemtrec 1-800-424-9300  
**Number**  
**Company Emergency Phone** 800-233-1294  
**Number**



**Precautionary Statements - Storage**

Store locked up  
Protect from sunlight. Store in a well-ventilated place  
Keep container tightly closed.  
Do not expose to temperatures exceeding 122°F (50°C)

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

None

**Other information**

• Toxic to aquatic life with long lasting effects

0.00002% of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Chemical Name</b>	<b>CAS-No</b>	<b>Weight %*</b>
PETROLEUM DISTILLATES	64742-47-8	40-50
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	20-30
KEROSENE	8008-20-6	20-30
NAPHTHENIC OIL, SEVERELY HYDROT	64742-52-5	10-20
2-BUTOXYETHANOL	111-76-2	1-10

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES**

**First aid measures for different exposure routes**

**General advice** Avoid contact with skin,eyes, and clothing.Avoid breathing, vapors,mist,or gas.

**Eye contact** In the case of contact with eyes, rinse immediately with plenty of water for 15 minutes and seek medical advice.

**Skin contact** Wash off immediately with plenty of water. If skin irritation persists, call a physician.

**Inhalation** Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.

**Ingestion** Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

**Most important symptoms/effects, acute and delayed**

**Main Symptoms** May cause skin irritation. Inhalation causing Central Nervous System effects. ingestion causing lung damage.

**Indication of immediate medical attention and special treatment needed, if necessary**

**Notes to physician** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES**

**Suitable Extinguishing Media**

water fog. Dry chemical. Carbon dioxide (CO2). Cool containers / tanks with water spray.

**Unsuitable Extinguishing Media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Flammable or extremely flammable aerosol. Container may burst in fire.

**Explosion Data**

**Sensitivity to Mechanical Impact** none.

**Sensitivity to Static Discharge** Yes.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use with adequate ventilation to keep the exposure levels below the OELS.

**Environmental precautions**

**Environmental precautions** Report spills as required by local and federal regulations.

**Methods and materials for containment and cleaning up**

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Contain liquid and collect with an inter,non-combustible material.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

**Conditions for safe storage, including any incompatibilities**

**Technical measures/Storage conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

**Incompatible products** Store away from strong oxidizers and acids.

**Aerosol Level** 3

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
---------------	-----------	----------	------------

PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> 106-97-8:TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup> 75-28-5:TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
KEROSENE 8008-20-6	TWA: 200 mg/m <sup>3</sup> total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures Skin - potential significant contribution to overall exposure by the cutaneous route	-	TWA: 100 mg/m <sup>3</sup>
2-BUTOXYETHANOL 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m <sup>3</sup>

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Exposure controls**

**Engineering Measures**

Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection**

Safety glasses with side-shields.

**Skin and body protection**

Chemical resistant apron. Protective gloves.

**Respiratory protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene measures**

Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Physical and chemical properties**

**Physical state**

Aerosol

**Appearance**

Clear

**Color**

amber

**Odor**

Light Vanilla Scent

**Odor Threshold**

No information available

**Property**

**Values**

**Remarks • Methods**

**pH**

No information available

**Melting/freezing point**

No information available

**Boiling point/boiling range**

No information available

**Flash Point**

-96.4 °C / -141 °F

Based on propellant

**Evaporation rate**

No information available

**Flammability (solid, gas)**

No information available

**Flammability Limits in Air**

<b>upper flammability limit</b>	No information available
<b>lower flammability limit</b>	No information available
<b>Vapor pressure</b>	No information available
<b>Vapor density</b>	No information available
<b>Specific Gravity</b>	0.749
<b>Water solubility</b>	Practically insoluble
<b>Partition coefficient: n-octanol/water</b>	No information available
<b>Autoignition temperature</b>	No information available
<b>Decomposition temperature</b>	No information available
<b>Viscosity</b>	No information available
<b>Explosive properties</b>	No information available

**Other information**

**VOC Content(%)** 89.17

**10. STABILITY AND REACTIVITY**

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Conditions to Avoid**

Extremes of temperature and direct sunlight.

**Incompatible Materials**

Store away from strong oxidizers and acids.

**Hazardous Decomposition Products**

Carbon oxides.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

<b>Product Information</b>	Product does not present an acute toxicity hazard based on known information
<b>Inhalation</b>	Exposure to high vapour concentrations may cause nervous systems effects such as headache, nausea, and dizziness.
<b>Eye contact</b>	May cause slight irritation.
<b>Skin contact</b>	Irritating to skin. Prolonged skin contact may defat the skin and produce dermatitis.
<b>Ingestion</b>	Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

**Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
PETROLEUM DISTILLATES 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
KEROSENE 8008-20-6	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.28 mg/L ( Rat ) 4 h
2-BUTOXYETHANOL 111-76-2	= 470 mg/kg ( Rat )	= 99 mg/kg ( Rabbit )	= 450 ppm ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea, and vomiting. May cause mild irritation. Irritating to skin. Prolonged or repeated exposure may cause dermatitis. Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** Irritating to skin.  
**Eye damage/irritation** Irritating to eyes.  
**Sensitization** No information available.  
**Germ Cell Mutagenicity** No information available.  
**Carcinogenicity** The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
KEROSENE 8008-20-6	A3	Group 3	-	-
2-BUTOXYETHANOL 111-76-2	A3	Group 3	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

**Reproductive toxicity** The ingredients are not reproductive hazards.  
**Specific target organ systemic toxicity (single exposure)** may cause drowsiness and dizziness.  
**Specific target organ systemic toxicity (repeated exposure)** No information available.  
**Chronic toxicity** Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest. Prolonged skin contact may defat the skin and produce dermatitis.  
**Target Organ Effects** Blood, Central nervous system, Eyes, Hematopoietic System, Kidney, Liver, Respiratory system, Skin.  
**Aspiration hazard** May be fatal if swallowed and enters airways.

**Numerical measures of toxicity - Product Information**

**Unknown Acute Toxicity** 0.00002% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 20458 mg/kg

**ATEmix (dermal)** 47881 mg/kg

**ATEmix (inhalation-dust/mist)** 65.3 mg/l

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
PETROLEUM DISTILLATES 64742-47-8	-	2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static 45 mg/L LC50 Pimephales promelas 96h flow-through	-	-
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	-	-	-	-

NAPHTHENIC OIL, SEVERELY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h
2-BUTOXYETHANOL 111-76-2	-	1490 mg/L LC50 Lepomis macrochirus 96h static 2950 mg/L LC50 Lepomis macrochirus 96h	-	1000 mg/L EC50 Daphnia magna 48h

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	<=2.8
2-BUTOXYETHANOL 111-76-2	0.81

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment**

**Waste Disposal Methods**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated packaging**

Do not re-use empty containers.

**14. TRANSPORT INFORMATION**

**DOT Ground**

CONSUMER COMMODITY ORM-D  
or  
LIMITED QUANTITY

**IATA**

UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

**IMDG**

UN1950, AEROSOLS, 2.1, LTD. QTY.

**15. REGULATORY INFORMATION**

**International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
PETROLEUM DISTILLATES	X	X	X	X	X	X	X	X
PROPANE/ISOBUTANE/N-BUTANE	X	X	X	Not listed	X	X	X	X
KEROSENE	X	X	X	X	X	X	X	X



**F00491 - 80-727 ELECTRO GUARD MOISTURE AND CORROSION BARRIER**

**Revision Date 25-Nov-2014**

NAPHTHENIC OIL, SEVERELY HYDROT	X	X	X	X	X	X	X	X
2-BUTOXYETHANOL	X	X	X	X	X	X	X	X

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**CHINA** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**U.S. Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
2-BUTOXYETHANOL - 111-76-2	111-76-2	1-10	1.0

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

**Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

**U.S. State Regulations**

**California Proposition 65**

No warning required.

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
KEROSENE 8008-20-6	X	X	X
2-BUTOXYETHANOL 111-76-2	X	X	X

**EPA Pesticide Registration Number** Not applicable

**Canada**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**16. OTHER INFORMATION**

<u>NFPA</u>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
<u>HMIS</u>	Health Hazard 2	Flammability 4	Physical Hazard 1	Personal protection B

**Prepared By** Regulatory Affairs  
**Issuing date** 25-Nov-2014  
**Revision Date** 25-Nov-2014

**Revision Note**  
No information available

**Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**