



## Safety Data Sheet

Copyright, 2015 Meguiar's, Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	26-6716-0	<b>Version Number:</b>	3.00
<b>Issue Date:</b>	03/20/15	<b>Supersedes Date:</b>	07/02/12

### SECTION 1: Identification

#### 1.1. Product identifier

M06, Mirror Glaze Liquid Cleaner Wax (21-151A);, M0616, M0664

#### Product Identification Numbers

14-1000-1159-3, 14-1000-1160-1, 14-1000-1161-9

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive, One-step application that cleans, polishes and protects

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	Meguiar's, Inc.
<b>DIVISION:</b>	Meguiar's
<b>ADDRESS:</b>	17991 Mitchell South, Irvine, CA 92614, USA
<b>Telephone:</b>	949-752-8000 (Fax: 949-752-5784)

#### 1.4. Emergency telephone number

CHEMTREC 1-800-424-9300 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Skin Corrosion/Irritation: Category 2.

Specific Target Organ Toxicity (central nervous system): Category 3.

#### 2.2. Label elements

##### Signal word

Warning

**Symbols**

Exclamation mark |

**Pictograms**



**Hazard Statements**

Causes skin irritation.  
 May cause drowsiness or dizziness.

**Precautionary Statements**

**General:**

Keep out of reach of children.

**Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves.  
 Wash thoroughly after handling.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 IF ON SKIN: Wash with plenty of soap and water.  
 If skin irritation occurs: Get medical advice/attention.  
 Take off contaminated clothing and wash it before reuse.  
 Call a POISON CENTER or doctor/physician if you feel unwell.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed.  
 Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Hazards not otherwise classified**

None.

1% of the mixture consists of ingredients of unknown acute oral toxicity.  
 9% of the mixture consists of ingredients of unknown acute dermal toxicity.  
 19% of the mixture consists of ingredients of unknown acute inhalation toxicity.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	60 - 90 Trade Secret *
Petroleum Distillate	64742-48-9	10 - 30 Trade Secret *
Petroleum Distillate	64742-47-8	3 - 7 Trade Secret *
Conditioners	Trade Secret*	< 5 Trade Secret *
Calcined Kaolin	92704-41-1	1 - 5 Trade Secret *
Poly(Dimethylsiloxane)	63148-62-9	1 - 5 Trade Secret *
White Mineral Oil (Petroleum)	8042-47-5	0.1 - 1 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### **If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide  
Carbon dioxide  
Irritant Vapors or Gases

#### Condition

During Combustion  
During Combustion  
During Combustion

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., Skin Notation
Petroleum Distillate	64742-47-8	CMRG	TWA:165 ppm	
Naphtha	64742-48-9	OSHA	TWA:400 mg/m3(100 ppm)	
Petroleum Distillate	64742-48-9	Manufacturer determined	TWA:100 ppm	
MINERAL OILS, HIGHLY-REFINED OILS	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
Paraffin oil	8042-47-5	OSHA	TWA(as mist):5 mg/m3	
White Mineral Oil (Petroleum)	8042-47-5	CMRG	TWA:5 mg/m3;STEL:10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists  
 AIHA : American Industrial Hygiene Association  
 CMRG : Chemical Manufacturer's Recommended Guidelines  
 OSHA : United States Department of Labor - Occupational Safety and Health Administration  
 TWA: Time-Weighted-Average  
 STEL: Short Term Exposure Limit  
 CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>General Physical Form:</b>	Liquid
<b>Odor, Color, Grade:</b>	Sweet odor; Creamy, ivory liquid
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	8.5 - 9.2
<b>Melting point</b>	<i>Not Applicable</i>
<b>Boiling Point</b>	390 °F
<b>Flash Point</b>	200 °F [ <i>Test Method: Pensky-Martens Closed Cup</i> ] [ <i>Details: D93-90</i> ]
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<i>No Data Available</i>
<b>Vapor Density</b>	<i>No Data Available</i>
<b>Density</b>	.96 g/cm <sup>3</sup>
<b>Specific Gravity</b>	0.96 [ <i>Ref Std: WATER=1</i> ]
<b>Solubility in Water</b>	Moderate
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>

Viscosity	23,000 - 33,000 centipoise
Volatile Organic Compounds	14.66 % weight
Volatile Organic Compounds	203.14 g/l
VOC Less H2O & Exempt Solvents	517.96 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

#### Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

**Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:**

**Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE > 50 mg/l
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Petroleum Distillate	Inhalation-Vapor		LC50 estimated to be 20 - 50 mg/l
Petroleum Distillate	Dermal	Rabbit	LD50 > 3,000 mg/kg
Petroleum Distillate	Ingestion	Rat	LD50 > 5,000 mg/kg
Calcined Kaolin	Ingestion	Rat	LD50 > 2,000 mg/kg
Petroleum Distillate	Dermal	Rabbit	LD50 > 3,160 mg/kg
Petroleum Distillate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3.0 mg/l
Petroleum Distillate	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly(Dimethylsiloxane)	Dermal	Rabbit	LD50 > 19,400 mg/kg
Poly(Dimethylsiloxane)	Ingestion	Rat	LD50 > 17,000 mg/kg
White Mineral Oil (Petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White Mineral Oil (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Petroleum Distillate	Rabbit	Irritant
Petroleum Distillate	Rabbit	Mild irritant
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Petroleum Distillate	Rabbit	No significant irritation
Petroleum Distillate	Rabbit	Mild irritant
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	Mild irritant

**Skin Sensitization**

Name	Species	Value
Petroleum Distillate	Guinea pig	Not sensitizing
Petroleum Distillate	Guinea pig	Not sensitizing
White Mineral Oil (Petroleum)	Guinea pig	Not sensitizing

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Petroleum Distillate	In vivo	Not mutagenic
Petroleum Distillate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Petroleum Distillate	In Vitro	Not mutagenic
White Mineral Oil (Petroleum)	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Petroleum Distillate	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Petroleum Distillate	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Petroleum Distillate	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
White Mineral Oil (Petroleum)	Dermal	Mouse	Not carcinogenic
White Mineral Oil (Petroleum)	Inhalation	Multiple animal species	Not carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Petroleum Distillate	Inhalation	Not toxic to development	Rat	NOAEL 2.4 mg/l	during organogenesis
White Mineral Oil (Petroleum)	Ingestion	Not toxic to female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not toxic to male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not toxic to development	Rat	NOAEL 4,350 mg/kg/day	during gestation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Petroleum Distillate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Petroleum Distillate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	



Petroleum Distillate	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 6.5 mg/l	4 hours
Petroleum Distillate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Petroleum Distillate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Petroleum Distillate	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 4.6 mg/l	6 months
Petroleum Distillate	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1.9 mg/l	13 weeks
Petroleum Distillate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.6 mg/l	90 days
Petroleum Distillate	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	All data are negative	Rat	NOAEL 5.6 mg/l	12 weeks
Petroleum Distillate	Inhalation	heart	All data are negative	Multiple animal species	NOAEL 1.3 mg/l	90 days
White Mineral Oil (Petroleum)	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,381 mg/kg/day	90 days
White Mineral Oil (Petroleum)	Ingestion	liver   immune system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,336 mg/kg/day	90 days

**Aspiration Hazard**

Name	Value
Petroleum Distillate	Aspiration hazard
Petroleum Distillate	Aspiration hazard
White Mineral Oil (Petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## SECTION 14: Transport Information

General Transportation Statement This product does not require classification by DOT, IATA, ICAO or IMDG.

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact manufacturer for more information

#### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

### 15.2. State Regulations

Contact manufacturer for more information

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact manufacturer for more information

### 15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

Health: 2 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	26-6716-0	Version Number:	3.00
Issue Date:	03/20/15	Supersedes Date:	07/02/12

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's, Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's, Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's, Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's, Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's, Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's, Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's, Inc.

**Meguiar's, Inc. USA SDSs are available at [www.Meguiars.com](http://www.Meguiars.com)**